

Republic of Iraq  
Ministry of Higher Education & Scientific Research  
University of Technology  
Chemical Engineering Department



## ***Prediction of Reaction Kinetics for Isomerization Unit in Al-Daura Refinery***

A research  
Submitted to the Department of Chemical Engineering, University  
of Technology as a Partial Fulfillment of the Requirements of the  
Degree of Higher Diploma in Chemical Engineering

By

***Rawnak Adnan Kadhim***

B.SC. in Chemical Engineering

Baghdad University


2005

Supervised by

***Assist. Prof. Dr. Adel Sharif Hamadi***

## **Abstract**

The present study focuses on the new technology for the isomerization of light naphtha used in Al-Daura refinery including the major guidelines (principals of the process, mechanism of the process, catalyst used, major elements of the unit, process variables), A kinetic model was derived for the prediction of the reaction kinetics of the isomerization reactions (the reaction rate constants  $K_1$  and  $K_2$  and activation energy  $E_a$ ) by using five different operating temperatures (120,135,150,165,180°C).



$$K_1 = \frac{F_A^o}{VC_A^o} \left[ \ln \frac{1}{1-X} (1+\varepsilon) - \varepsilon X \right] \frac{T}{T_o}$$

$$C_{\text{iso}} = C_A^o \left[ 1 - \exp(-K_1 t) - \frac{K_1}{K_2 - K_1} \left[ \exp(-K_1 t) - \exp(-K_2 t) \right] \right]$$

And using Arrhenius equation for determination of activation energy  $E_a$

$$\ln K_1 = \ln K_o - \frac{E_a}{RT}$$

## ***Abstract***

---

The five mentioned operating temperatures were applied in the kinetic model in the range of activation of the used catalyst (pt/Al<sub>2</sub>O<sub>3</sub>-Cl), a mass balance calculations was done on the unit for kinetics prediction purpose, the results of the model show that the values of the activation energy were relatively small indicating that the reactions were towards the formation of isomers, and that  $k_1$  values proportional directly with the temperature.

$$E_a \text{ of } nC_6 < E_a \text{ of } nC_5 < E_a \text{ of } CH \\ (1525.74) \quad (2738.82) \quad (2880.394)$$

Also the present study show that the effect of blending different isomerase portions (10, 20, 30, 40, 50 % vol.) with the prepared gasoline pool on the final octane number of the final gasoline pool and comparing the gasoline pool (with the mentioned isomerase portions) with different gasoline kinds, such as premium gasoline and leaded gasoline according to the values of research octane number (RON).